



MS-35000 SERIES CONTINUOUS HINGES

MS No.	Leaf				Dash No. - Open Width																			
	Thickness	Knuckle	Pin Dia.	Length	-1	-2	-3	-4	-5	-6	-7	-8	-9	-10	-11	-12	-13	-14	-15	-16	-17	-18	-19	-20
MS-35821	.032	.50	.063	72						.75	1	1.06	1.25	1.5										
MS-35822	.040	.50	.091	72									1.06	1.25	1.5	2								
	.040	.62	.091	72.50													1.06	1.25	1.5	2				
MS-35823	.050	.62	.125	72.50					1.06	1.5	2	2.5												
MS-35825	.060	.62	.125	85									1.06	1.5	2	2.5								
	.060	1	.125	84													1.06	1.5	2	2.5				
MS-35826	.060	1	.187	84									1.06	1.5	2	2.5								
	.060	2	.187	84													1.06	1.5	2	2.5				
MS-35829	.075	2	.187	84											2	2.5	3	3.5	4					
	.075	2	.250	84																2	2.5	3	3.5	4
MS-35830	.090	2	.250	84											3	3.5	4	5						
	.090	2	.312	84					4	5	6													
	.090	2	.375	84																				
MS-35831	.125	2	.312	84	4	5													4	5	6			
	.125	2	.375	84						4	5	6												

Notes: 1. The MS part number consists of the MS No. plus the Dash No. followed by the applicable letter for material, i.e., MS35821-6A or MS35821-8D.
 2. Materials are available in A aluminum, B brass leaf & copper pin, C stainless steel leaf & pin, D plain steel leaf & pin, and E plain steel leaf, cadmium-plated & brass pin.
 3. When protective finish is required for D materials, add F to the dash number, i.e., MS35821-8DF.
 4. See Military Specifications for more detailed information on materials and finishes.

A-A-55000 SERIES CONTINUOUS HINGES

MS No.	Leaf				Dash No. - Open Width																			
	Thickness	Knuckle	Pin Dia.	Length	-1	-2	-3	-4	-5	-6	-7	-8	-9	-10	-11	-12	-13	-14	-15	-16	-17	-18	-19	-20
A-A-55589	.032	.50	.063	72						.75	1	1.06	1.25	1.5										
A-A-55590	.040	.50	.091	72									1.06	1.25	1.5	2								
	.040	.62	.091	72.50													1.06	1.25	1.5	2				
A-A-55591	.050	.62	.125	72.50					1.06	1.5	2	2.5												
A-A-55592	.060	.62	.125	85									1.06	1.5	2	2.5								
	.060	1	.125	84													1.06	1.5	2	2.5				
A-A-55593	.060	1	.187	84									1.06	1.5	2	2.5								
	.060	2	.187	84													1.06	1.5	2	2.5				
A-A-55594	.075	2	.187	84											2	2.5	3	3.5	4					
	.075	2	.250	84																2	2.5	3	3.5	4
A-A-55595	.090	2	.250	84											3	3.5	4	5						
	.090	2	.312	84					4	5	6													
	.090	2	.375	84																				
A-A-55596	.125	2	.312	84	4	5													4	5	6			
	.125	2	.375	84						4	5	6												

Notes: 1. The AA part number consists of the AA No. plus the Dash No. followed by the applicable letter for material, i.e., AA55589-6A or AA55589-8D.
 2. Materials are available in A aluminum, B brass leaf & copper pin, C stainless steel leaf & pin, D plain steel leaf & pin, and E plain steel leaf, cadmium-plated & brass pin.
 3. C materials will be supplied with passivated leaves.
 4. When protective finish is required for D materials, add F to the dash number, i.e., AA55589-8DF.
 5. See Military Specifications for more detailed information on materials and finishes.

COMPRESSION SPRING CATCH AND STRIKE

Part No.	Overall Length	Maximum Width	Holes	Material	Finish
MS18015002 (Catch)	Per MS	Per MS	.128	Steel & Stainless	Zinc with Yellow Chromate
MS18015003 (Strike)	Per MS	Per MS	.128	Steel & Stainless	Zinc with Yellow Chromate

Note: One (1) MS-18015-2 (Catch) and one (1) MS-18015-3 (Strike) equals one (1) MS-18015-1.