




- Barreled ends for greater holding power.
- Smooth, rounded edges ensure that Lockit Clips won't cut into cable's insulation—or the installer's hand.
- Releasable and reusable loops for easy wire bundling.
- Locking ends twist into place with fingertip pressure.
- Part Description Key: LL XXX, where XXX = Maximum Bundle Diameter (inches).



- Part Description Key (part numbers **4155** thru **4172** only): PMLL XX-YY, where XX = Maximum Bundle Diameter (inches) and YY = Height Above Panel (inches).




HEYClip™ Lockit™ Loops

Standard Loops

| MAXIMUM BUNDLE DIAMETER | | PART NO. Natural | DESCRIPTION | OVERALL HEIGHT C | |
|-------------------------|------|---------------------|-------------|------------------|------|
| in. | mm. | | | in. | mm. |
| LL Series | | | | | |
| .25 | 6,4 | 3793 | LL 250 | .84 | 21,2 |
| .38 | 9,5 | 3795 | LL 375 | 1.02 | 25,9 |
| .50 | 12,7 | 3797 | LL 500 | 1.20 | 30,4 |
| .75 | 19,1 | 3799 | LL 750 | 1.45 | 36,8 |

Standard color natural.



Standoff Loops - Arrowhead Mount

| MAXIMUM BUNDLE DIAMETER | | PART NO. Natural | DESCRIPTION | HEIGHT ABOVE PANEL C | | MOUNTING HOLE DIAMETER | |
|--|------|---------------------|-------------|----------------------|------|------------------------|-----|
| in. | mm. | | | in. | mm. | in. | mm. |
| PMLL Series For Panels from .03" (0,8 mm) - .08" (2,0 mm) thick | | | | | | | |
| .28 | 7,0 | 4155 | PMLL 28-19 | .19 | 4,8 | .236 | 6,0 |
| | | 4156 | PMLL 28-50 | .50 | 12,7 | | |
| | | 4157 | PMLL 28-75 | .75 | 19,1 | | |
| | | 4158 | PMLL 28-100 | 1.00 | 25,4 | | |
| .39 | 10,0 | 4160 | PMLL 39-19 | .19 | 4,8 | | |
| | | 4161 | PMLL 39-50 | .50 | 12,7 | | |
| | | 4162 | PMLL 39-75 | .75 | 19,1 | | |
| | | 4163 | PMLL 39-100 | 1.00 | 25,4 | | |
| .50 | 12,5 | 4165 | PMLL 50-19 | .19 | 4,8 | | |
| | | 4166 | PMLL 50-50 | .50 | 12,7 | | |
| | | 4167 | PMLL 50-75 | .75 | 19,1 | | |
| | | 4168 | PMLL 50-100 | 1.00 | 25,4 | | |
| .59 | 15,0 | 4170 | PMLL 59-19 | .19 | 4,8 | | |
| | | 4171 | PMLL 59-50 | .50 | 12,7 | | |
| | | 4172 | PMLL 59-75 | .75 | 19,1 | | |
| | | 4173 | PMLL 59-100 | 1.00 | 25,4 | | |
| For Panels up to .09" (2,4 mm) thick | | | | | | | |
| .25 | 6,4 | 3778 | PMLL 250 | .93 | 23,6 | .185 | 4,7 |
| .38 | 9,5 | 3779 | PMLL 375 | 1.11 | 28,2 | | |
| .50 | 12,7 | 3780 | PMLL 500 | 1.26 | 32,0 | | |
| .75 | 19,1 | 3782 | PMLL 750 | 1.55 | 39,4 | | |
| For Panels up to .06" (1,5 mm) thick | | | | | | | |
| 1.00 | 25,4 | 3796 | PMLL 1000 | 2.22 | 56,4 | .250 | 6,4 |

Standard color natural.

Quick Specs

| | |
|---------------------|----------------------------|
| Material | Nylon 6/6 |
| Flammability Rating | 94V-2 |
| Temperature Range | 32°F (0°C) to 185°F (85°C) |