




HEYClip™ Nylon Tension Wire Clips

Adhesive-Back Mount

- Gather and direct cables singly or in groups smaller than those accommodated by other Heyco Wire Holders.
- WCA-5 may also be screw mounted. #6 screws not included.
- Nylon 6/6 with a 94V-2 flammability rating.
- Apply to a clean, dry surface.

WIRE CAPACITY		PART NO.		DESCRIPTION	FOOTPRINT		OVERALL HEIGHT	
in.	mm.	Natural	Black		in.	mm.	in.	mm.
.125 x .250	3,2 x 6,4	3638	3638B	WC A-4	.63 x .63	15,9 x 15,9	.25	6,4
.125 x .500	3,2 x 12,7	3639	3639B	WC A-5	1.00 x 1.13	25,4 x 28,6	.31	7,9
BUNDLE DIAMETER								
.190	4,8	3629	3629B	WC A-43	.63 x .63	15,9 x 15,9	.31	7,9
.250	6,4	3636	3636B	WC A-44	.63 x .63	15,9 x 15,9	.38	9,5
.375	9,5	3637	3637B	WC A-46	.75 x .75	19,1 x 19,1	.50	12,7

Standard color natural.



Heyclip™ “U” Style Wire Clip

Adhesive-Back Mount




- Manufactured from a UL listed vinyl for fire and flame resistance.
- The compact design combined with a strong acrylic based adhesive provides a low cost means of routing a .250” (6 mm) diameter cable or tubing.
- Temperature range of 0° F (-18° C) to 150° F (66° C). Recommended storage temperature from 60° F (16° C) to 80° F (27° C), and approximately relative humidity of 50%.

WIRE CAPACITY		PART NO.	DESCRIPTION	FOOTPRINT		OVERALL HEIGHT	
in.	mm.			Gray	B x C		D**
				in.	mm.	in.	mm.
.125	3,2	tbd	WCUA 125	.75 x .75	19,1 x 19,1	.28	7,1
.250	6,4	3792	WCUA 250	.75 x .75	19,1 x 19,1	.47	11,9
.375	9,5	tbd	WCUA 375	.75 x .75	19,1 x 19,1	.59	15,1
.500	12,7	tbd	WCUA 500	1.00 x 1.00	25,4 x 25,4	.69	17,5
.562	14,3	tbd	WCUA 562	1.00 x 1.00	25,4 x 25,4	.75	19,1
.750	19,1	tbd	WCUA 750	1.00 x 1.00	25,4 x 25,4	.91	23,0

Standard color natural.

*Custom lengths available by special order, consult Heyco.

**At maximum wire capacity.



Quick Specs

Material	Tension Wire Clips Nylon 6/6	Material	“U” Style Wire Clips PVC
Flammability Rating	94V-2	Tape	1/16” Double-side adhesive with white liner