





HEYClip[™] SunRunner 4[™] Cable Clip

Double-Compression Design for Panels up to .250" (6,4 mm) Thick

C	PANEL THICKNESS CLAMPING RANGE Minimum Maximum			WIRE DIA. RANGE Maximum	PART NO.	DESCRIPTION	FOOTPRINT A x B		OVERALL HEIGHT C	
in.	mm.	in.	mm.	(4) Wires			in.	mm.	in.	mm.
.125	3,2	.250	6,4	.20" (5,1 mm)- .30" (7,6 mm)	′	SunRunner 4 [™] 100 Pack	1.34 x .50	34,0 x 12,7	.36	9,1
				each cable	S6440	SunRunner 4™ Bulk				





SunRunner 4™

SunRunner® 90°





- Designed to hold up to (4) 12 gauge USE-2 or (4) 10 gauge PV-1000V solar wires.
- Also for use with other types of cables from .20" (5,1 mm) to .30" (7,6 mm) in diameter.
- Designed to provide a better method for PV module wire management and may be used whenever multiple cable management is needed.
- Smooth clip edges prevent damage to cable insulation.
- SunRunner 4 Cable Clip is designed to accommodate thicker racking systems up to .250" (6,4 mm) thick.
- Constructed from heat treated 410 stainless steel for excellent strength and corrosion protection for outdoor exposure.
- For additional HEYClips in Stainless Steel see pages 1-13 and 1-14.

HEYClip[™] SunRunner[®] 90° Cable Clip

Double-Compression, Right Angle Design

PANEL TH CLAMPIN Minimum		G RANGE Maximum		WIRE DIA. RANGE Maximum	PART NO.	DESCRIPTION	FOOTPRINT A x B		OVERALL HEIGHT C		
	in.	mm.	in.	mm.	(1) Wire			in.	mm.	in.	mm.
.055	055	1.4	.125	3.2	.20" (5,1 mm)- .30" (7,6 mm)	S6406	SunRunner 90° 100 Pack	.65 x .78	16.5 x 19.8	.39	9,9
	1,4	.123	3,2	each cable	S6446	SunRunner 90° Bulk	.03 X .70	10,5 x 19,6	.39	9,9	





Material

SunRunner 4 – .020" thick heat treated 410 stainless steel SunRunner 90° – .025" thick 304 stainless steel



- SunRunner 90° Cable Clip is designed to mount at a 90° angle to the original SunRunner. The SunRunner 90° will accommodate a single cable from .20" (5,1 mm) to .30" (7,6 mm).
- SunRunner 90° is designed for use with PV modules mounted in the landscape mode. PV modules with shorter than normal junction box cables cannot be dressed out to the sides of the module. The SunRunner 90° will allow the junction box cables to be run to the adjacent modules across the short side of the PV module frame.

