



# Heyco® Liquid Tight Hole Plugs

## Standard 85 Durometer Plugs

Maximum Panel Thickness .125" (3,2 mm)

- Oil tight, rain tight, submersible.
- UL certified for outdoor applications.
- V0 Flammability rating.
- Install with fingertip pressure (no tool required).
- Multiple nominal sizes fit .500" (12,7 mm) to 1.00" (25,4 mm) true size mounting holes.
- Three trade sizes fit 1/2" to 1" knock-out holes.
- Lock firmly in boxes from .030" (0,8 mm) to .125" (3,2 mm) thick.
- True sizes are UL recognized under Underwriters' Laboratories File E51579 and CSA certified by Canadian Standard Association File 008919C.
- Trade sizes are UL listed under Underwriters' Laboratories File E51579 and CSA certified by Canadian Standard Association File 081067C.

MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	UL or V0	PART DIMENSIONS					
in.	mm.				A Head Diameter		B Overall Height		C Head Thickness	
.500	12,7	<b>3830</b>	KOS-LT 500	UL	.91	23,1	.45	11,4	.29	7,4
.625	15,9	<b>3834</b>	KOS-LT 625	UL	1.03	26,2	.47	11,9	.31	7,9
.750	19,1	<b>3831</b>	KOS-LT 750	UL	1.15	29,2	.51	13,0	.35	8,9
.875	22,2	<b>3833</b>	KOS-LT 1/2	UL	1.23	32,5	.50	13,5	.36	9,1
1.000	25,4	<b>3832</b>	KOS-LT 1000	UL	1.41	35,8	.56	14,2	.40	10,2
1.093	27,8	<b>3835</b>	KOS-LT 3/4	UL	1.53	38,6	.55	14,0		
1.375	34,9	<b>3837</b>	KOS-LT 1	UL	1.80	45,2	.56	14,3	.42	10,7

Available in black color only.



## Low 75 Durometer Plugs

Maximum Panel Thickness .125" (3,2 mm)

MOUNTING HOLE DIAMETER*		PART NO.		DESCRIPTION	UL or V0	PART DIMENSIONS					
in.	mm.	Black	Gray			B Head Diameter		C Overall Height		Head Thickness	
.875	22,2	<b>3833FN</b>	<b>3833FP</b>	KOS-LT 1/2 LD	UL	1.23	32,5	.50	13,5	.36	9,1
1.093	27,8	<b>3835FN</b>	<b>3835FP</b>	KOS-LT 3/4 LD	UL	1.53	38,6	.55	14,0	.40	10,2
1.375	34,9	<b>3837FN</b>	<b>3837FP</b>	KOS-LT 1 LD	UL	1.80	45,2	.56	14,3	.42	10,7

Standard colors black and gray.

\*Consult Heyco for other Liquid Tight Hole Plug sizes in Low Durometer material.



Quick Specs

Material	85 75	Santoprene-Hardness 85 Shore A Santoprene-Hardness 75 Shore A
Certifications	Trade Sizes (1/2, 3/4, 1) True Sizes (all other)	UL Listed under Underwriters' Laboratories File E28430 CSA Certified by Canadian Standard Association File 081067C UL Recognized under Underwriters' Laboratories File E51579 CSA Certified by Canadian Standard Association File 0089118C
Flammability Rating		94V-0
Temperature Rating		-81°F (-60°C) to 275°F (135°C)