





## Heyco® Lockit™ Hose Clamps

- Retainer clip allows clamp to be **pre-positioned** on hose before final installation.
- Double row of teeth for more secure grip.
- Quick and easy installation. Tighten instantly with hand pliers or Air Tool (below).
- Reusable. Can be removed without cutting.
- Supertough nylon clamps offer additional clamping strength.
- Outlast tubing under pressure.
- Lightweight yet resist corrosion, salt water, weak acids, grease, and common solvents.
- Non-conductive and non-magnetic.
- No moving pieces to seize or vibrate loose.
- Material: Nylon 6/6
- Flammability Rating: 94HB
- Material Temperature Index: 257°F (125°C) maximum temperature on part not to exceed 221°F (105°C)
- Maximum Pressure Rating: 200 psi

EFFECTIVE CLAMP RANGE				PART NO.  Black	DESCRIPTION	PART DIMENSIONS			
Minimum Diameter		Maximum Diameter				A Clamp Thickness		B Strap Thickness	
in.	mm.	in.	mm.			in.	mm.	in.	mm.
.344	8,7	.406	10,3	<b>2388</b>	LHC 344	.250	6,4	.080	2,0
.531	13,5	.593	15,1	<b>2391</b>	LHC 531				
.671	17,0	.812	20,6	<b>2393</b>	LHC 672				

Standard color black.



## Heyco® Pneumatic Air Tool for Nylon Hose Clamps

for PART NO.		HOSE CLAMP DESCRIPTION	AIR TOOL PART NO. INCLUDING JAWS	JAW PART NO.*	
Std.	Lockit			Upper	Lower
2302	-	HC 250	0170	0T83	0T84
2306	<b>2388</b>	HC 344			
2310	-	HC 406			
2314	-	HC 468			
2318	<b>2391</b>	HC 531			
2322	-	HC 593			
2326	<b>2393</b>	HC 672			
2330	-	HC 750			
2334	-	HC 875			
2338	-	HC 953			
2342	-	HC 1031			
2346	-	HC 1250			
2350	-	HC 1406			
2354	-	HC 1593			
2358	-	HC 1687			
2362	-	HC 1875			

\*Jaw part number if purchased separately.



- Allows for a **semi-automated process** which increases speed over manual tools.
- Activated by hand lever reducing stress on the hand and the risk of carpal tunnel syndrome associated with repetitive assembly.
- Adjustable jaws allow tool to accommodate a wide range of Heyco Hose Clamps.
- Operates only when lever is depressed.
- Tool operates on standard shop air.
- Maximum Pressure Rating: 125 psi