



Heyco® Nylon Knock-Out Seals and Thick Panel Knock-Out Seals



Mounting Hole Diameter Range: 1/2" to 2" Electrical Knock-outs (.875" to 2.500" nominal)

| MOUNTING HOLE DIAMETER | | TRADE SIZE | PART NO. Silver Gray | DESCRIPTION | PART DIMENSIONS | | | |
|------------------------|-----|------------|-------------------------|-------------|--------------------|--|---------------------|--|
| in. | mm. | | | | A Head Diameter | | B Overall Height | |
| | | | | | | | | |

Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)

| | | | | | | | | |
|-------|------|-------|------|-----------|------|------|-----|------|
| .875 | 22,2 | 1/2 | 3997 | KOS 1/2 | 1.02 | 25,8 | | |
| 1.093 | 27,8 | 3/4 | 3998 | KOS 3/4 | 1.22 | 31,0 | | |
| 1.375 | 34,9 | 1 | 3999 | KOS 1 | 1.50 | 38,1 | .45 | 11,5 |
| 1.750 | 44,5 | 1-1/4 | 4000 | KOS 1-1/4 | 1.91 | 48,4 | | |
| 2.000 | 50,8 | 1-1/2 | 4001 | KOS 1-1/2 | 2.16 | 54,9 | | |

Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)

| | | | | | | | | |
|-------|------|-------|------|------------|------|------|-----|------|
| .875 | 22,2 | 1/2 | 3991 | KOST 1/2 | 1.02 | 25,8 | | |
| 1.093 | 27,8 | 3/4 | 3992 | KOST 3/4 | 1.22 | 31,0 | | |
| 1.375 | 34,9 | 1 | 3993 | KOST 1 | 1.50 | 38,1 | .56 | 14,3 |
| 1.750 | 44,5 | 1-1/4 | 3994 | KOST 1-1/4 | 1.91 | 48,4 | | |
| 2.000 | 50,8 | 1-1/2 | 3995 | KOST 1-1/2 | 2.16 | 54,9 | .58 | 14,7 |
| 2.500 | 63,5 | 2 | 4002 | KOS 2 | 2.73 | 69,3 | .75 | 19,1 |

Standard color silver gray.

- **Plug electrical knock-outs.**
- Molded in silver gray color to resemble galvanized steel.
- Install quickly with fingertip pressure (no tool required).
- Economical.
- Multiple trade sizes fit 1/2" to 2" knock-out holes.
- Lock firmly in boxes up to 1/8" thick, except for Part Number 4002 (KOS 2) and Thick Panel Knock-Out Seals (KOST's) which lock firmly in boxes up to 1/4" thick.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Approximate Head Thickness: .062" (1,6 mm). Thickness may vary.
- To adapt a Knock-Out to accept a Heyco Strain Relief, see page 4-37 for Knock-Out Adapters.

Heyco® Nylon V-0 Knock-Out Seals

Multiple Locking Steps for Panel Thickness up to .125" (3,2 mm)
Mounting Hole Diameter Range: 1/2" to 1-1/2" Electrical Knock-outs (.875" to 2.000" nominal)



| MOUNTING HOLE DIAMETER | | TRADE SIZE | PART NO. Silver Gray | DESCRIPTION | PART DIMENSIONS | | | |
|------------------------|-----|------------|-------------------------|-------------|--------------------|--|---------------------|--|
| in. | mm. | | | | A Head Diameter | | B Overall Height | |
| | | | | | | | | |

| | | | | | | | | |
|-------|------|-------|------|----------|------|------|-----|------|
| .875 | 22,2 | 1/2 | 2706 | HFP 875 | 1.02 | 25,8 | | |
| 1.093 | 27,8 | 3/4 | 2729 | HFP 1093 | 1.22 | 31,0 | | |
| 1.375 | 34,9 | 1 | 2759 | HFP 1375 | 1.50 | 38,1 | .45 | 11,5 |
| 1.750 | 44,5 | 1-1/4 | 2779 | HFP 1750 | 1.91 | 48,4 | | |
| 2.000 | 50,8 | 1-1/2 | 2789 | HFP 2000 | 2.16 | 54,9 | | |

Standard color black.

- **Molded from a nylon material which, in the event of a fire, will not burn and will not produce toxic gases.** Also formulated for sunlight resistance.

| | |
|----------------------------|---|
| Material | Nylon 6/6 |
| Certifications | Recognized under the Component Program of Underwriters' Laboratories, File E51579 Certified by Canadian Standards Association, File 8919 |
| Flammability Rating | KOS: 94V-2, HFP 94V-0 |
| Temperature Rating | -40°F (-40°C) to 221°F (105°C) |

Quick Specs