



Heyco® Nylon Nytye® Mounting Platforms

- Multiple sizes, strengths, and mounting options anchor Nytyes® securely.

- Four styles:


- 1) Adhesive-Backed only
- 2) Adhesive-Backed with Screw Mount option
- 3) Push Mount
- 4) Screw Mount only

- Rubber based adhesive effective up to 126°F (52°C).


- Apply Adhesive-Backed parts to a clean, dry surface.

NYTYE MIN. TENSILE STRENGTH		MOUNTING STYLE	SCREW SIZE		NYTYE INSERT POINTS	PART NO.	DESCRIPTION	FOOTPRINT	
lbs.	N		no.	mm.				Natural	in.
40	178	Adhesive only	-	-	4	3594	MP 4A-S	.80 x .80	20,3 x 20,3
50	222	Adhesive/Screw	8	4,0	2	3590	MP 2A	1.10 x 1.10	27,9 x 27,9
		Adhesive/Screw	6	3,5	4	3593	MP 4A	1.15 x 1.15	29,2 x 29,2
		Push Mounts into .250" (6,4 mm) dia. hole	-	-	2	3762	MP PM-250	.31 x .56	7,9 x 14,3
50	222	Screw only	8	4,0	2	3759	MP S-68	.38 x .63	9,5 x 15,9
120	534	Screw only	10	5,0	2	3753	MP S-10	.63 x .88	15,9 x 22,2
n/a	n/a	Push Mount Threaded Rod	5/8	16,0	2	3754	MP S-5/8	1.25 x 2.31	31,8 x 58,7


Standard color natural.



MP-4A-S




MP-2A




MP-4A



MP-PM-250



MP-S-68
MP-S-10



MP-S-5/8

Heyco® Cable Tie Tensioning Tool

- Part No. 0998 fits all standard duty Nytyes. Metal construction, has three tension settings, and automatically trims excess.



Quick Specs

Material	Nylon 6/6
Flammability Rating	94V-2
Temperature Rating	185°F (85°C)