



Heyco® Nytye® Nylon Cable Ties

Regular Nytyes

- Smooth, radiused edges ensure that Nytyes won't cut into the cable's insulation—or the installer's hand.
- One-piece design reduces cost and installation time.
- Nytyes feature a bent tip for ease of pickup and insertion around small bundles. V-shaped raised ridges on the tip provide a sure grip.
- Close, evenly spaced teeth permit fine adjustment—from .025" (0,6 mm) on the smallest Nytyes to .063" (1,6 mm) on the largest.

Screw Mountable Nytyes

- Molded-in screw hole mount provides one-piece mounting and bundling.
- Mounting screws not included.


Push Mountable Nytyes

- Snap quickly into holes with only fingertip pressure.
- Provide one-piece mounting and bundling.
- Hold securely in panels up to 1/8" (3,2 mm) thick.





PART SPECIFICATIONS				PART NO.		DESCRIPTION	PART DIMENSIONS							
Min. Tensile Strength lbs.	N	Max. Bundle Diameter in. mm.		Natural	UV Black		A Length in. mm.		B Width in. mm.		C Thickness in. mm.		Min Bundle Diameter in. mm.	
Regular Nytyes®														
18	80	.75	19,1	3500	3502	NT 70	3.80	97	.09	2,3	.045	1,1	.062	1,6
		1.50	38,1	3503	3504	NT 70L	6.25	159						
		2.00	50,8	3506	3507	NT 70E	8.00	203						
30	133	1.00	25,4	3510	3511	NT 90	5.20	132	.12	2,9	.055	1,4		
		1.25	31,8	3515	3516	NT 120	5.67	144	.14	3,4				
40	178	2.00	50,8	3850	3851	NT 170	8.25	210	.14	3,4	.050	1,3		
		1.75	44,4	3520	3521	NT 150	7.50	191	.19	4,8	.055	1,4		
3.00	76,2	3525	3526	NT 250	11.25	286								
Screw Mountable Nytyes®														
Screw #														
30	133	1.00	25,4	3550	-	MNT 90	5.50	140	.115	2,9	.045	1,1	4	
40	178	1.25	31,8	3555	-	MNT 120	6.50	165	.135	3,4	.050	1,3	8	
50	222	1.75	44,4	3560	-	MNT 150	8.00	203	.190	4,8	.055	1,4	10	
Push Mountable Nytyes®														
Mounting Hole Dia.														
40	180	1.42	36,0	-	3907	PWMS-155 HSB	6.23	158	.14	3,5	.047	1,2	.19	4,6
50	222	1.75	44,4	3904	-	PMT 150	8.00	203	.19	4,8	.055	1,4	.25	6,4


Standard color natural.



Regular Nytyes



Screw Mountable Nytyes



Push Mountable Nytyes



Quick Specs

Material
Certifications

Nylon 6/6
Recognized under the Component Program of Underwriters' Laboratories File E54523

Flammability Rating
Temperature Rating

94V-2
185°F (85°C)