



# Heyco® Original Series-35 Liquid Tight Cordgrips

Straight-Thru, PG Hubs, in HEYConvenient Small Packs





CABLE DIA. RANGE				PART NO.		DESCRIPTION	UL or RA	SMALL PACK	PART DIMENSIONS									
Minimum		Maximum		Black	Gray				A Clearance Hole Dia.	B Max. O.A. Length		C Thread Length		D Wrenching Nut Thk.		E Flat Size		
in.	mm.	in.	mm.			in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.			
.064	1,6	.210	5,3	<b>4040</b>	<b>4041</b>	RLTF 7	RA	100	.492	12,5	1.17	29,7	.33	8,4	.20	5,1	.59	15,0
.114	2,9	.250	6,4	<b>4042</b>	<b>4043</b>	LTF 7												
.069	1,8	.187	4,7	<b>4044</b>	<b>4045</b>	RLTF 9	RA	100	.599	15,2	1.30	33,0	.34	8,6	.20	5,1	.75	19,1
.181	4,6	.312	7,9	<b>4046</b>	<b>4047</b>	LTF 9												
.069	1,8	.250	6,6	<b>4048</b>	<b>4049</b>	RLTF 11	RA	100	.733	18,6	1.46	37,1	.39	9,9	.20	5,1	.86	21,8
.230	5,8	.395	10,0	<b>4050</b>	<b>4051</b>	LTF 11												
.170	4,3	.450	11,4	<b>4054</b>	<b>4055</b>	LTF 13.5	UL	100	.804	20,4	1.53	38,9	.41	10,4	.20	5,1	.95	24,1
.230	5,8	.530	13,9	<b>4058</b>	<b>4059</b>	LTF 16	UL	50	.886	22,5	1.66	42,2	.45	11,4	.23	5,8	1.05	26,7
.250	6,4	.490	12,4	<b>4060</b>	<b>4061</b>	RLTF 21	UL	50	1.115	28,3	1.87	47,5	.52	13,2	.23	5,8	1.30	33,0
.450	11,4	.705	17,9	<b>4062</b>	<b>4063</b>	LTF 21												
.590	15,0	.990	25,1	<b>4066</b>	<b>4067</b>	LTF 29	UL	25	1.470	37,3	2.23	56,6	.59	15,0	.28	7,1	1.66	42,2

Standard colors black and gray.

For larger sizes, see Heyco-Tite Liquid Tight Cordgrips on page 3-3.

- Wide range of approved cable diameters.
- IP 68 rated.
- Acme threads on body prevent skipping and speed installation.
- For use in clearance or threaded holes.
- All nylon construction with TPE sealing gland resists salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents. (This feature is not assessed by UL.)
- PG hub threads are steel conduit threads per DIN 40430, see page 3-49.
- Multiple sizes for flexible cord diameters ranging from .064" (1,6 mm) to .990" (25,1 mm). For larger sizes, see Heyco-Tite Liquid Tight Cordgrips on page 3-3.
- We recommend using the fitting with the smallest maximum diameter that will fit your application.
- **Unassembled Nylon Locknuts INCLUDED.**
- For Heyco Liquid Tight Threaded Plugs, see page 3-43.
- Consult Heyco for cordgrips molded in other colors.



SUGGESTED CLEARANCE HOLE FOR NONTHEADED MOUNTING

Material	Nylon 6/6 with TPE Sealing Gland
Certifications	<ul style="list-style-type: none"> <li>UL Listed under Underwriters' Laboratories File E51579</li> <li>RA Recognized under the Component Program of Underwriters' Laboratories File E51579</li> <li>CS Certified by Canadian Standards Association File 93876C</li> </ul>
Flammability Rating	94V-2
Temperature Rating	Static -40°F (-40°C) to 239°F (115°C) Dynamic -4°F (-20°C) to 212°F (100°C)
IP Rating	IP 68 (70 PSI, 5 BAR)

Quick  
Specs