





Heyco® Lockit™ Hose Clamps

- Retainer clip allows clamp to be **pre-positioned** on hose before final installation.
- Double row of teeth for more secure grip.
- Quick and easy installation. Tighten instantly with hand pliers or Air Tool (below).
- Reusable. Can be removed without cutting.
- Supertough nylon clamps offer additional clamping strength.
- Outlast tubing under pressure.
- Lightweight yet resist corrosion, salt water, weak acids, grease, and common solvents.
- Non-conductive and non-magnetic.
- No moving pieces to seize or vibrate loose.
- Material: Nylon 6/6
- Flammability Rating: 94HB
- Material Temperature Index: 257°F (125°C) maximum temperature on part not to exceed 221°F (105°C)
- Maximum Pressure Rating: 200 psi

EFFECTIVE CLAMP RANGE				PART NO. Black	DESCRIPTION	PART DIMENSIONS			
Minimum Diameter		Maximum Diameter				A Clamp Thickness		B Strap Thickness	
in.	mm.	in.	mm.			in.	mm.	in.	mm.
.344	8,7	.406	10,3	2388	LHC 344	.250	6,4	.080	2,0
.531	13,5	.593	15,1	2391	LHC 531				
.671	17,0	.812	20,6	2393	LHC 672				

Standard color black.



Heyco® Pneumatic Air Tool for Nylon Hose Clamps

for PART NO.		HOSE CLAMP DESCRIPTION	AIR TOOL PART NO. INCLUDING JAWS	JAW PART NO.*	
Std.	Lockit			Upper	Lower
2302	-	HC 250	0170	0T83	0T84
2306	2388	HC 344			
2310	-	HC 406			
2314	-	HC 468			
2318	2391	HC 531			
2322	-	HC 593			
2326	2393	HC 672			
2330	-	HC 750			
2334	-	HC 875			
2338	-	HC 953			
2342	-	HC 1031			
2346	-	HC 1250			
2350	-	HC 1406			
2354	-	HC 1593			
2358	-	HC 1687			
2362	-	HC 1875			

*Jaw part number if purchased separately.



- Allows for a **semi-automated process** which increases speed over manual tools.
- Activated by hand lever reducing stress on the hand and the risk of carpal tunnel syndrome associated with repetitive assembly.
- Adjustable jaws allow tool to accommodate a wide range of Heyco Hose Clamps.
- Operates only when lever is depressed.
- Tool operates on standard shop air.
- Maximum Pressure Rating: 125 psi