



# Heyco® Snap-In Cordgrip Strain Reliefs – Straight-Thru

*The Ultimate in Snap-In Strain Relief Protection*


For Panels from .062” (1,6 mm) to .125” (3,2 mm) Thick

- **Unique fingers securely lock into a range of panel sizes without use of locknut.**
- Smooth, rounded interior edges for ease of installation.
- Limited intrusion into enclosure where access is tight.
- Rotation prevented when used in Double D mounting holes.
- Easy to install—no tools required.
- Ratchet design of sealing nut assembly provides superior anti-vibration and ensures a firm grip on the cable.
- Available in multiple sizes for cable diameters ranging from .065” (1,7 mm) to 1.560” (39,6 mm).
- We recommend using the fitting with the smallest maximum diameter that will fit your application.
- Meet UL strain relief requirements without bending or kinking the cable.
- For Foam Washers, see page 2-15.
- Though similar in appearance and function to Heyco-Tite Liquid Tight Cordgrips, Snap-In Cordgrip Strain Reliefs may not be liquid tight at the panel interface. For our complete range of **Liquid Tight** Cordgrips with Integral Sealing Ring, see Section 3.
- Use Heyco **Mounting Hole Plugs** for DD Mounting Holes, or **Heyco Dome Plugs** for round Mounting Holes, to fill blank/unused Mounting Holes and thus allow for a single panel design across multiple applications. See Section 6.

WILL FIT THESE CABLES				PART NO.	DESCRIPTION	UL or RA	PANEL DIMENSIONS				Mounting Hole Plug Part No.		
Minimum Diameter		Maximum Diameter					A Mounting Hole	B To Prevent Rotation		C Max O.A. Length			
in.	mm.	in.	mm.	Black		in.	mm.	in.	mm.	in.	mm.		
.065	1,7	.220	5,6	<b>M4802</b>	RSCG 500	RA	.500	12,7	.450	11,4	1.21	30,7	2491
.115	2,9	.250	6,4	<b>M4800</b>	SCG 500								
.065	1,7	.187	4,8	<b>M4808</b>	RSCG 625	RA	.625	15,9	.550	14,0	1.30	33,0	2497
.105	2,7	.312	7,9	<b>M4806</b>	SCG 625								
.069	1,8	.250	6,4	<b>M4814</b>	RSCG 750	RA	.750	19,1	.660	16,8	1.48	37,6	2503
.230	5,8	.395	10,0	<b>M4812</b>	SCG 750								
.095	2,4	.260	6,6	<b>M4820</b>	RSCG 875	RA	.875	22,2	.770	19,6	1.46	37,1	2509
.170	4,3	.450	11,4	<b>M4818</b>	SCG 875								
.180	4,6	.440	11,2	<b>M4826</b>	RSCG 1000	RA	1.000	25,4	.875	22,2	1.62	41,1	2713*
.260	6,6	.546	13,9	<b>M4824</b>	SCG 1000								
.250	6,4	.485	12,3	<b>M4832</b>	RSCG 1093	RA	1.093	27,8	.970	24,6	1.75	44,5	2717
.485	12,3	.709	18,0	<b>M4830</b>	SCG 1093								
.250	6,4	.485	12,3	<b>M4838</b>	RSCG 1125	UL	1.125	28,6	1.000	25,4	1.75	44,5	2717
.485	12,3	.709	18,0	<b>M4836</b>	SCG 1125								
.490	12,4	.787	20,0	<b>M4844</b>	RSCG 1250	RA	1.250	31,8	1.125	28,6	2.05	52,1	2740*
.590	15,0	.920	23,4	<b>M4842</b>	SCG 1250								
.490	12,4	.787	20,0	<b>M4850</b>	RSCG 1375	RA	1.375	34,9	1.250	31,8	2.05	52,1	2753*
.590	15,0	1.000	25,4	<b>M4848</b>	SCG 1375								
.787	20,0	1.020	25,9	<b>M4856</b>	RSCG 1500	RA	1.500	38,1	1.375	34,9	2.23	56,6	2763*
.865	22,0	1.180	30,0	<b>M4854</b>	SCG 1500								
.787	20,0	1.020	25,9	<b>M4862</b>	RSCG 1750	RA	1.750	44,5	1.625	41,3	2.28	57,9	2773*
.865	22,0	1.260	32,0	<b>M4860</b>	SCG 1750								
1.000	25,4	1.240	31,5	<b>M4868</b>	RSCG 2000	RA	2.000	50,8	1.875	47,6	2.41	61,2	2959
1.230	31,2	1.560	39,6	<b>M4866</b>	SCG 2000								
1.160	29,5	1.350	34,3	<b>M4874</b>	RSCG 2375	RA	2.375	60,3	2.250	57,2	2.50	63,5	consult Heyco
1.450	36,8	1.560	39,6	<b>M4872</b>	SCG 2375								

Standard color black.

\*For round Mounting Hole only. For DD Mounting Hole Plug, consult Heyco.



SUGGESTED CLEARANCE HOLE FOR NONTHEADED MOUNTING

Quick Specs

Material  
Certifications

Nylon 6/6 w/Buna N Sealing Gland  
 Recognized under Underwriters' Laboratories File E51579  
 Certified by Canadian Standards Association File 093876

Flammability Rating  
Temperature Rating

94V-2  
-22°F (-30°C) to 212°F (100°C)