



Heyco® -Tite Aluminum Liquid Tight Cordgrips

Straight-Thru, NPT Hubs




The Ultimate in Liquid Tight Strain Relief Protection



CABLE DIA. RANGE				PART NO.	THREAD SIZE	UL	PART DIMENSIONS							
Minimum		Maximum					Machined Aluminum	A Clearance Hole Dia.		B Max. O.A. Length		C Thread Length		D Wrenching Flat Size
in.	mm.	in.	mm.		in.	mm.		in.	mm.	in.	mm.	in.	mm.	
.125	3,2	.188	4,8	M5029	NPT 3/4	UL	1.09	27,7	1.62	41,1	.56	14,2	1.13	28,7
.188	4,8	.250	6,4	M5030										
.250	6,4	.312	7,9	M5031										
.312	7,9	.375	9,5	M5032										
.375	9,5	.438	11,1	M5033										
.438	11,1	.500	12,7	M5034										
.500	12,7	.562	14,3	M5035										
.562	14,3	.625	15,9	M5036										
.438	11,1	.500	12,7	M5037										
.500	12,7	.562	14,3	M5038										
.562	14,3	.625	15,9	M5039	NPT 3/4	UL	1.09	27,7	1.82	46,2	.56	14,2	1.37	34,8
.562	14,3	.688	17,5	M5040										
.625	15,9	.750	19,1	M5041										
.688	17,5	.812	20,6	M5042										
.438	11,1	.562	14,3	M5050	NPT 1	UL	1.38	35,1	2.03	51,6	.62	15,7	1.56	39,6
.562	14,3	.625	15,9	M5051										
.562	14,3	.688	17,5	M5052										
.625	15,9	.750	19,1	M5053										
.688	17,5	.812	20,6	M5054										
.750	19,1	.875	22,2	M5055										
.812	20,6	.938	23,8	M5056										
.875	22,2	1.000	25,4	M5057*										
.875	22,2	1.000	25,4	M5058										
1.000	25,4	1.125	28,6	M5059	NPT 1	UL	1.38	35,1	2.5	63,5	.69	17,5	2.25	57,2
1.125	28,6	1.120	31,8	M5060										
1.250	31,8	1.375	34,9	M5061										

- **Aluminum construction** provides excellent durability and performance for most **industrial applications**.
- For use in both indoor and outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture, and coolants.
- IP 67 rated.
- Approved for NEMA 6 applications.
- Protect cable from damage and pull-out and are used in conduit hubs or knock-outs at the point where the electrical cable is to be terminated.
- Unique design with a combination tightening surface that includes both a hex area and a knurled surface.
- Anti-friction washer allows for easier compression.

Assembled O-ring **INCLUDED**. *Not UL Listed or CSA Certified.
Locknut not included - See page 3-40 for Metal Locknuts.



SUGGESTED CLEARANCE HOLE FOR NON-THREADED MOUNTING

Material
Certifications

- Aluminum with Neoprene Sealing Gland and Viton® O-Ring
- UL Listed under Underwriters' Laboratories File E51579
- CSA Certified by Canadian Standard Association File 258093
- Approved for NEMA 6 Applications

Flammability Rating
Temperature Rating
IP Rating

94V-2
-40°F (-40°C) to 250°F (121°C)
IP 67

Quick Specs