




Heyco®-Tite Cast Aluminum Liquid Tight Cordgrips

Right Angle, NPT Hubs


The Ultimate in Liquid Tight Strain Relief Protection Sweep Design



- **Aluminum construction** provides excellent durability and performance for most **industrial applications**.
- For use in both indoor and outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture, and coolants.
- IP 67 rated.
- Approved for NEMA 6 applications.
- Protect cable from damage and pull-out and are used in conduit hubs or knock-outs at the point where the electrical cable is to be terminated.
- Unique design with a combination tightening surface that includes both a hex area and a knurled surface.
- Anti-friction washer allows for easier compression.



SUGGESTED CLEARANCE HOLE FOR NON-THREADED MOUNTING



CABLE DIA. RANGE				PART NO.	THREAD SIZE	UL	PART DIMENSIONS							
Minimum		Maximum					Machined Aluminum	A Clearance Hole Dia.		B Max. O.A. Length		C Thread Length		D Wrenching Flat Size
in.	mm.	in.	mm.			in.		mm.	in.	mm.	in.	mm.	in.	mm.
.125	3,2	.188	4,8	M5230	NPT 3/8	UL	.68	17,3	2.00	50,8	.44	11,2	.88	23,4
.188	4,8	.250	6,4	M5231										
.250	6,4	.312	7,9	M5232										
.312	7,9	.375	9,5	M5233										
.375	9,5	.438	11,1	M5234										
.125	3,2	.188	4,8	M5235	NPT 1/2	UL	.88	22,3	2.39	60,7	.56	14,2	1.13	28,7
.188	4,8	.250	6,4	M5236										
.250	6,4	.312	7,9	M5237										
.312	7,9	.375	9,5	M5238										
.375	9,5	.438	11,1	M5239										
.438	11,1	.500	12,7	M5240	NPT 3/4	UL	1.09	27,7	2.88	73,2	.59	15,0	1.37	31,8
.500	12,7	.562	14,3	M5241										
.562	14,3	.625	15,9	M5242										
.438	11,1	.500	12,7	M5243										
.500	12,7	.562	14,3	M5244										
.500	12,7	.625	15,9	M5245	NPT 1	UL	1.38	35,0	3.13	79,5	.60	15,2	1.56	39,6
.562	14,3	.688	17,5	M5246										
.625	15,9	.750	19,1	M5247										
.688	17,5	.812	20,6	M5248										
.500	12,7	.562	14,3	M5249										
.500	12,7	.625	15,9	M5250										
.562	14,3	.688	17,5	M5251										
.625	15,9	.750	19,1	M5252										
.688	17,5	.812	20,6	M5253										
.750	19,1	.875	22,2	M5254										
.812	20,6	.938	23,8	M5255										
.875	22,2	1.000	25,4	M5256										

O-ring not included - See pages 2-13 through 2-15 for Sealing Washers, Foam Washers & Thermoplastic O-rings.
Locknut not included - See page 3-40 for Metal Locknuts.

Quick Specs

Material Certifications

Aluminum with Neoprene Sealing Gland and Viton® O-Ring
 UL Listed under Underwriters' Laboratories File E51579
 SP Certified by Canadian Standard Association File 258093
 Approved for NEMA 6 Applications

Flammability Rating
Temperature Rating
IP Rating

94V-2
 -40°F (-40°C) to 250°F (121°C)
 IP 67