



Heyco® -Tite Cast Aluminum Liquid Tight Cordgrips

ALL NEW PRODUCTS!






Straight-Thru, NPT Hubs

The Ultimate in Liquid Tight Strain Relief Protection

CABLE DIA. RANGE				PART NO. Cast Aluminum	THREAD SIZE	UL	PART DIMENSIONS								
Minimum		Maximum					A		B		C		D		
in.	mm.	in.	mm.				Clearance Hole Dia.	in.	mm.	Max. O.A. Length	in.	mm.	Thread Length	in.	mm.
1.688	42,9	1.812	46,0	M5091	NPT 2-1/2	UL	2.96	75,2	4.20	106,7	1.28	32,5	4.00	101,6	
1.812	46,0	1.938	49,2	M5092											
1.938	49,2	2.062	52,4	M5093											
2.062	52,4	2.188	55,6	M5094											
2.188	55,6	2.312	58,7	M5095											
2.312	58,7	2.438	61,9	M5096											
1.688	42,9	1.812	46,0	M5097	NPT 3	UL	3.58	90,9	4.20	106,7	1.31	33,3	4.00	101,6	
1.812	46,0	1.938	49,2	M5098											
1.938	49,2	2.062	52,4	M5099											
2.062	52,4	2.188	55,6	M5100											
2.188	55,6	2.312	58,7	M5101											
2.312	58,7	2.438	61,9	M5102											
2.437	61,9	2.625	66,7	M5103	NPT 3	*	3.50	88,9	4.85	123,2	1.39	35,3	4.75	120,7	
2.625	66,7	2.812	71,4	M5104											
2.812	71,4	3.000	76,2	M5105											
3.000	76,2	3.250	82,6	M5106											

Assembled O-ring **INCLUDED**. *Not UL Listed or CSA Certified.
Locknut not included - See page 3-40 for Metal Locknuts.

- **Aluminum construction** provides excellent durability and performance for most **industrial applications**.
- For use in both indoor and outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture, and coolants.
- IP 67 rated.
- Approved for NEMA 6 applications.
- Protect cable from damage and pull-out and are used in conduit hubs or knock-outs at the point where the electrical cable is to be terminated.
- Unique design with a combination tightening surface that includes both a hex area and a knurled surface.
- Anti-friction washer allows for easier compression.



SUGGESTED CLEARANCE HOLE FOR NON-THREADED MOUNTING

Material Certifications

- Aluminum with Neoprene Sealing Gland and Viton® O-Ring
- UL Listed under Underwriters' Laboratories File E51579
- CSA Certified by Canadian Standard Association File 258093
- Approved for NEMA 6 Applications

Flammability Rating
Temperature Rating
IP Rating

94V-2
-40°F (-40°C) to 250°F (121°C)
IP 67

Quick Specs