



Heyco® -Tite Liquid Tight Cordgrips

Multi-Hole with Integral Sealing Ring
Sequenced by Conductor Size

The Ultimate in Liquid Tight Strain Relief Protection

**NO O-RING
 REQUIRED!**



| CONDUCTORS | | NPT HUB* | | PG HUB** | | METRIC HUB** | | |
|---|-----|-------------|----------------|-------------|----------------|--------------|----------------|-------------|
| Hole Size mm. | No. | UL or cULus | Black Part No. | Desc. | Black Part No. | Desc. | Black Part No. | Desc. |
| Round, Open Holes - consult Heyco for Snap-in-2 Hub versions | | | | | | | | |
| 4,2 | 2 | | M3231GAB | LTCG 1/2 | M3216GAB | LTCG 13 | M4340GAB | LTCG M20 |
| 4,5 | 9 | cULus | M8437GBF | LTCG 1 | M3225GBF | LTCG 29 | M4348GBF | LTCG M32 |
| | 13 | cULus | M4524GBG | LTCG 1-1/4 | M3204GBG | LTCG 36 | M4352GBG | LTCG M40 |
| 4,6 | 3 | | M3234GBD | LTCG 3/4 | M3222GBD | LTCG 21 | M4344GBD | LTCG M25 |
| | 4 | | M3234GBE | LTCG 3/4 | M3222GBE | LTCG 21 | M4344GBE | LTCG M25 |
| 5,0 | 2 | | M3231GAC | LTCG 1/2 | M3216GAC | LTCG 13 | M4340GAC | LTCG M20 |
| | 4 | | M3234GAD | LTCG 3/4 | M3222GAD | LTCG 21 | M4344GAD | LTCG M25 |
| 5,2 | 2 | UL | M3231GAE† | LTCG 1/2 | M3216GAE | LTCG 13 | M4340GAE†† | LTCG M20 |
| | 3 | UL | M3234GAF† | LTCG 3/4 | M3222GAF | LTCG 21 | M4344GAF | LTCG M25 |
| | 4 | UL | M3234GAG† | LTCG 3/4 | M3222GAG | LTCG 21 | M4344GAG | LTCG M25 |
| 5,6 | 3 | UL | M3200GAH† | LTCG LL 1/2 | M3219GAH | LTCG 16 | M3198GAH | LTCG LL M20 |
| 6,0 | 2 | | M3200GAJ | LTCG LL 1/2 | M3219GAJ | LTCG 16 | M3198GAJ | LTCG LL M20 |
| | 4 | | M3234GBC | LTCG 3/4 | M3222GBC | LTCG 21 | M4344GBC | LTCG M25 |
| 6,5 | 6 | | M8437GAL | LTCG 1 | M3225GAL | LTCG 29 | M4348GAL | LTCG M32 |
| | | | M4524GAL | LTCG 1-1/4 | M3204GAL | LTCG 36 | M4352GAL | LTCG M40 |
| 7,0 | 3 | | M3234GAM | LTCG 3/4 | M3222GAM | LTCG 21 | M4344GAM | LTCG M25 |
| 7,4 | 2 | | M3234GAN | LTCG 3/4 | M3222GAN | LTCG 21 | M4344GAN | LTCG M25 |
| 8,0 | 2 | | M3234GAQ | LTCG 3/4 | M3222GAQ | LTCG 21 | M4344GAQ | LTCG M25 |
| | 6 | | M4524GAR | LTCG 1-1/4 | M3204GAR | LTCG 36 | M4352GAR | LTCG M40 |
| 9,0 | 4 | | M8437GAS | LTCG 1 | M3225GAS | LTCG 29 | M4348GAS | LTCG M32 |
| | 5 | | M4524GAT | LTCG 1-1/4 | M3204GAT | LTCG 36 | M4352GAT | LTCG M40 |
| | 7 | | M4524GAW | LTCG 1-1/4 | M3204GAW | LTCG 36 | M4352GAW | LTCG M40 |
| 9,5 | 4 | | M8437GAX | LTCG 1 | M3225GAX | LTCG 29 | M4348GAX | LTCG M32 |

Standard color black.

*Locknuts not included. For Locknut specifications or to order Locknuts separately, see pages 3-39 & 3-40.

**Unassembled Nylon Locknuts INCLUDED.

†Assembled Metal Locknut INCLUDED

††M4340GAE is UL approved under File E51579



- Heyco® Multi-hole glands provide the widest range of conductor through-hole size and number configurations, many of which are agency approved. See the tabular charts for specific approvals for specific parts. These approvals are not “global” or implied approvals; they are both real and part specific.
- Integral Sealing Ring ensures a superior seal at the clearance or threaded mounting hole location, every time.
- IP 68 rated.
- Cordgrips are made of nylon construction with TPE sealing glands that resist salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents.
- For body part dimensions see page 3-1, 3-3, and 3-4.
- Multi-hole glands are only to be used with Heyco Liquid Tight Cordgrips and are not sold separately.
- Consult Heyco for Cordgrips molded in other colors.

| | |
|---------------------|---|
| Material | Nylon 6/6 with TPE Sealing Gland |
| Certifications | UL Listed under Underwriters’ Laboratories File E51579 cULus Recognized under the Component Program of Underwriters’ Laboratories File E51579 to both Canadian and U.S. requirements |
| Flammability Rating | 94V-2 Standard |
| Temperature Rating | -22°F (-30°C) to 212°F (100°C) |
| IP Rating | IP 68 |

Quick Specs