PHYSICAL INFRASTRUCTURE SYSTEMS

System **Overview**

В. Copper Systems

C. Fiber **Optic** Systems

D. Power over Ethernet

E. Zone Cabling

F. Wireless

G. Outlets

Media Distribution

Physical Infrastructure Management J.

١.

Underfloor Routing

Overhead &

Surface Raceway

Cabinets, Racks & Cable Management

Grounding & Bonding

Industrial

Labeling & Identification

Cable Management Accessories

Q. Index

) PanZone® Wireless Access Point Enclosures

- Specifically designed for use with Cisco^ and other popular Wireless Access Points
- Lockable enclosure protects against tampering, vandalism, and theft
- Knockouts allow multiple antenna configurations
- Integrated ceiling bezel allows unit to replace 2' x 2'
- · Optional ceiling bracket kit allows WAP to be mounted in-ceiling for design flexibility for optimum wireless coverage
- 2' x 2' ceiling bracket eliminates cutting the ceiling tile by replacing a standard 2' x 2' ceiling tile



PZWC35E



PZWC35I



PZWC35



PZWIFIEN



PZWIFIENA





| Part Number | Part Description | Color | Std. Pkg. Qty. |
|-------------|---|-------|----------------------|
| PZWC35E | losures Designed for Use with Cisco Aironet^ Series Wireless Acc PanZone™ Wireless Access Point Enclosure for surface mount or for use in suspended ceilings with optional in-ceiling mounting bracket. Accommodates Cisco Aironet^ 1260 and 3500E Series Wireless Access Points. UL 2043 rated. Dimensions: 13.75"H x 12.0"W x 3.1"D (349.8 mm x 304.8 mm x 78.0mm) | White | ints 1 |
| PZWC35I | PanZone® Wireless Access Point Enclosure; accommodates Cisco Aironet^ 1140 and 3500 Series Wireless Access Points. UL 2043 rated. Dimensions: 23.8"H x 23.8"W x 3.1"D (603mm x 603mm x 78mm). | White | 1 |
| PZWC35 | PanZone® Wireless Access Point Enclosure for surface mount or for use in suspended ceilings with optional in-ceiling mounting bracket. Accommodates Cisco Aironet^ 1140 and 3500 Series Wireless Access Points. UL 2043 rated. Dimensions: 13.75"H x 12.0"W x 3.1"D | White | 1 |
| PZWIFIEN | PanZone® Wireless Access Point Enclosure; accommodates Cisco Aironet^ 1250 Series Wireless Access Points. UL 2043 rated. Dimensions: 13.75"H x 12.00"W x 4.75"D (349.8mm x 304.8mm x 120.6mm). | White | 1 |
| PZWIFIENA | PanZone® Wireless Access Point Enclosure; compatible with all Cisco Aironet^ 1250 Series WAPs when used with Cisco Patch Antennas (AIR-ANT5140V-R and/or AIR-ANT2430V-R). UL 2043 rated. Dimensions: 13.75"H x 12.00"W x 4.75"D (349.8mm x 304.8mm x 120.6mm). | White | 1 |
| PZWIFIED | PanZone® Wireless Access Point Enclosure; accommodates Cisco Aironet^ 1230 and 1240 Series Wireless Access Points. UL 2043 rated. Dimensions: 13.75"H x 12.00"W x 3.06"D (349.8mm x 304.8mm x 77.7mm). | White | 1 |
| PZWIFIEA | PanZone® Wireless Access Point Enclosure; compatible with all Cisco Aironet^ 1200, 1230, and 1240 Series WAPs when used with Cisco Patch Antennas (AIR-ANT5145V-R and/or AIR-ANT5959). UL 2043 rated. Dimensions: 13.75"H x 12.00"W x 3.06"D (349.8mm x 304.8mm x 77.7mm). | White | 1 |
| PZWIFIE | PanZone® Wireless Access Point Enclosure; accommodates Cisco Aironet^ 1200 Series Wireless Access Points. UL 2043 rated. Dimensions: 12.00"H x 12.00"W x 2.31"D | White | 1 |

^Cisco, SMARTnet, and Aironet are registered trademarks of Cisco Technology, Inc. For shielded versions of PanZone® Wireless Access Point Enclosures, add suffix "S" to part number.

(304.8mm x 304.8mm x 58.7mm).

PZWIFIEW

PZWRKA

PZWIFIEH

PZWIFIDCB

B. Copper Systems

C. Fiber Optic Systems

D. Power over Ethernet

E. Zone Cabling



G. Outlets

H. Media Distribution

I. Physical Infrastructure Management

J. Overhead & Underfloor Routing

K. Surface Raceway

Cabinets, Racks & Cable Management

M. Grounding & Bonding

> N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> Q. Index



Wireless Enclosures Designed for Use with Cisco Aironet[^] Series Wireless Access Points (continued)

| (continued) | | | | |
|-------------|---|-------|---|--|
| PZWIFIEW | PanZone® Wireless Access Point Enclosure with windowed front door; accommodates Cisco Aironet^ 1130 Series Wireless Access Points. Dimensions: 12.00"H x 12.00"W x 2.31"D (304.8mm x 304.8mm x 58.7mm). | White | 1 | |
| PZWIFIER | PanZone® Wireless Access Point Enclosure; accommodates Aruba AP-124 and AP-125 Wireless Access Point. UL 2043 rated. Dimensions: 13.75"H x 12.00"W x 3.06"D (349.8mm X 304.8mm X 77.7mm) | White | 1 | |
| PZWRKA | PanZone® Wireless Access Point Enclosure Retrofit Kit for PZWIFIEA and PZWIFIED enclosures to upgrade to Cisco^ 1140, 3500 802.11/n access points. Internal Bracket Dimensions: 5.8"H x 5.8"W x 1.7"D (147mm x 147mm x 44mm) Door Dimension: 13.6"H x 11.9"W x .3"D (346mm x 303mm x 8mm) | White | 1 | |

Wireless Enclosure Designed for HP, Foundry Networks‡, Enterasys Networks^, and Aruba^ Wireless Access Points

| PZWIFIEH | PanZone® Wireless Access Point Enclosure; accommodates HP ProCurve* 420, Foundry‡ IP200, and Enterasys^ RBT-4102 Wireless Access Points. UL 2043 rated. | White | 1 |
|----------|---|-------|---|
| | Dimensions: 13.75"H X 12.00"W X 3.06"D | | |
| | (349.8mm X 304.8mm X 77.7mm). | | |

In-Ceiling Mounting Bracket Kits

| PZWIFICB | PanZone® Wireless Enclosure In-Ceiling Mounting Bracket Kit for PZWIFIE and PZWIFIEW. Dimensions: 3.31"H x 13.62"W x .75"D (84.1mm x 345.9mm x 19.0mm). | White | 1 | |
|-----------|--|-------|---|--|
| PZWIFIDCB | PanZone® Wireless Enclosure In-Ceiling Mounting Bracket Kit for PZWIFIEN, PZWIFIENA, PZWIFIED, PZWIFIEA and PZWIFIEH. Dimensions: 4.06"H x 13.73"W x .81"D (103.1mm x 348.7mm x 20.6mm). | White | 1 | |
| PZW2X2CB | PanZone® Wireless Enclosure 2x2 ft. In-Ceiling Mounting Bracket Kit for PZWIFIE and PZWIFIEW. Dimensions: 3.19"H x 23.75"W x 23.75"D (81.1mm x 603.3mm x 603.3mm). | White | 1 | |
| PZW2X2DCB | PanZone® Wireless Enclosure 2x2 ft. In-Ceiling Mounting Bracket Kit for PZWIFIEN, PZWIFIENA, PZWIFIED, PZWIFIEA, and PZWIFIEH. Dimensions: 3.94"H x 23.75"W x 23.75"D (100.1mm x 603.3mm x 603.3mm). | White | 1 | |

^Cisco, SMARTnet, and Aironet are registered trademarks of Cisco Technology, Inc.

For shielded versions of PanZone® Wireless Access Point Enclosures, add suffix "S" to part number.





^{*}ProCurve is a registered trademark of Hewlett-Packard Development Company, L.P.

[‡]Foundry is a registered trademark of Foundry Networks, Inc.

[^]Enterasys is a registered trademark of Enterasys Networks, Inc.

^{^^^}Aruba is a registered trademark of Aruba Networks, Inc.



PHYSICAL INFRASTRUCTURE SYSTEMS

System **Overview**

> В. Copper Systems

C. Fiber **Optic** Systems

D. Power over Ethernet

E. Zone Cabling

F. Wireless

G. **Outlets**

Media Distribution

١. Physical Infrastructure Management

J. Overhead & Underfloor Routing

> Surface Raceway

Cabinets, Racks & Cable Management

Grounding & Bonding

Industrial

0. Labeling & Identification

Cable Management Accessories

> Q. Index

PanZone® NEMA 4X/IP66 Rated Wireless Access Point Enclosures

- NEMA 4X and IP66 rating protects against corrosion, windblown dust and rain, splashing water and hose-directed water
- Universal design accommodates the most popular Wireless Access Points including Cisco Aironet^ 1200, 1230, 1240, 1250, 1300, 1142, and 3500 Series and Aruba^^ 92, 105 and 134
- Fiberglass construction and aluminum mounting plate allow quick and easy access point installation
- UL508A Listed and approved

- · Include pre-configured mounting template
- Provisions for padlocks to protect against tampering and
- Optional NEMA 4X rated fittings available in various sizes
- · Optional NEMA 4X drain and vent kit
- Connectivity accessory kit (included): 2-position outlet box, Mini-Com® TX6™ PLUS Jack Module, TX6™ PLUS Patch Cord, silicone sealant and grounding cable
- · Shielded connectivity accessory kit also available



PZNWE12



PZNWE14

| Part Number | Part Description | Std. Pkg. Qty. |
|-------------|--|----------------------|
| PanZone® NE | MA 4X/IP66 Rated Wireless Access Point Enclosures | |
| PZNWE12 | Wireless enclosure designed for Power over Ethernet applications. Includes UTP connectivity kit. External dimensions: 13.56"H x 13.47"W x 6.56"D (344.4mm x 342.1mm x 166.6mm). Internal dimensions: 11.70"H x 11.70"W x 6.29"D (297.2mm x 297.2mm x 159.8mm). | 1 |
| PZNWE12S | Wireless enclosure designed for Power over Ethernet applications. Includes shielded connectivity kit. External dimensions: 13.56"H x 13.47"W x 6.56"D (344.4mm x 342.1mm x 166.6mm). Internal dimensions: 11.70"H x 11.70"W x 6.29"D (297.2mm x 297.2mm x 159.8mm). | 1 |
| PZNWE14 | Wireless enclosure designed for traditional AC power applications. Includes UTP connectivity kit. External dimensions: 15.50"H x 13.50"W x 6.25"D (393.7mm x 342.9mm x 158.8mm). Internal dimensions: 13.53"H x 11.55"W x 5.94"D (343.7mm x 293.4mm x 150.9mm). | 1 |
| PZNWE14S | Wireless enclosure designed for traditional AC power applications. Includes shielded connectivity kit. External dimensions: 15.50"H x 13.50"W x 6.25"D (393.7mm x 342.9mm x 158.8mm). Internal dimensions: 13.53"H x 11.55"W x 5.94"D (343.7mm x 293.4mm x 150.9mm). | 1 |
| NEMA 4X Rat | ed Fittings and Accessories | |

NEMA 4X Hated Fittings and Accessories

| PZNF1 | NEMA 4X rated compression fitting, ideal for cable diameters of .115" to .250" (2.82mm to 6.35mm). | 1 |
|--------|---|---|
| PZNF2 | NEMA 4X rated compression fitting, ideal for cable diameters of .230" to .395" (5.84mm to 10.03mm). | 1 |
| PZNF3 | NEMA 4X rated compression fitting, ideal for cable diameters of .170" to .450" (4.32mm to 11.43). | 1 |
| PZNDVK | NEMA 4X drain and vent kit. | 1 |

[^]Cisco and Aironet are registered trademarks of Cisco Systems, Inc.

[^] Aruba is a registered trademark of Aruba Networks, Inc.