# **Mighty Mount**<sup>™</sup> Leveling Mounts

Mighty Mount<sup>TM</sup> is the ideal solution for mounting heavy industrial equipment. Thirteen different sizes are available with load capacities ranging up to 12,500 lbs. Machinery life is extended through the use of a one-inch thick elastomer pad that provides a high level of shock and vibration isolation. Mighty Mount<sup>TM</sup> is often used on sensitive computerized equipment to isolate the equipment from external shock and vibration. With their sturdy, reliable construction and powder coated safety yellow finish, Mighty Mount<sup>TM</sup> will provide years of reliable and economical service.



#### **Common Applications:**

Injection molding machines
Die casting machines
Vibration-sensitive equipment
Drill presses
CNC machines
Punch presses
Press brakes
CMM instruments

### **Specifications:**


Meets OSHA anchoring standards High strength steel housing with yellow powder coated finish High-density non-skid elastomer base for vibration control Steel zinc plated stud







# **Mighty Mount**™ **Leveling Mounts**





### $\textbf{Mighty Mount}^{\text{\tiny{IM}}} \ \textbf{Leveling Mounts}$

P/N	Thread (A)	Base Dia (B)	Thread Length (C)	Base Height (D)	Min Load (lbs)	Max Load (lbs)	Natural Frequency (Hz)	Ship Wt. (lbs)
MM5028A	1/4-28	2	1 3/4	1	50	300	14	0.32
MM5016B	3/8-16	2	3	1	50	300	14	0.40
MM5024B	3/8-24	2	3	1	50	300	14	0.40
MM80163	3/8-16	3	3	1 1/2	300	700	8	1.14
MM80243	3/8-24	3	3	1 1/2	300	700	8	1.14
MM80136	1/2-13	3	6	1 1/2	300	700	8	1.46
MM120135	1/2-13	5	5	1 1/2	500	2000	8	2.76
MM120118	5/8-11	5	8	1 1/2	500	2000	8	3.26
MM160135	1/2-13	6	5	1 5/8	1000	4500	8	5.14
MM160105	3/4-10	6	5	1 5/8	1000	4500	8	5.60
MM160108	3/4-10	6	8	1 5/8	1000	4500	8	5.82
MM230105	3/4-10	9	5	2 1/2	4000	12500	9	15.22
MM230148	1-14	9	8	2 1/2	4000	12500	9	15.92





1-800-453-1692 www.aboveboardelectronics.com