

# Polyglass Filled Nylon Tube End Adaptors

S&W's NEW Polyglass Filled Nylon Tube End Adaptors support more weight for a fraction of the cost of traditional brass plugged designs. S&W has spent six months and invested heavily in testing and support for this revolutionary new product. The polyglass material is stronger and more resilient. To use, simply hammer the product into the end of the commonly used pipes and tubes which support frames, support that won't crack, break, or fall apart (using manufacturer recommended guidelines). S&W tube end adaptors will work with the entire line of PolyMount™, Level-It®, Anti-Vibe® and Glide-Rite™ levelers, mounts, and glides.


One Piece Design

Laboratory Tested

Heavy Duty

Supports up to 3500 lbs.


Corrosion Resistant (No Metal Parts)



## Square

P/N	Thread (A)	O.D. (B)	Tube Gauge Shape	Tube Outside Dia.	Tube Wall
TEN1-2A	3/8-16	1.5 sq.	16 ga. square	1.5 sq.	.065
TEN1-2B	1/2-13	1.5 sq.	16 ga. square	1.5 sq.	.065
TEN1-2C	5/8-11	1.5 sq.	16 ga. square	1.5 sq.	.065
TEN1-2D	3/4-10	1.5 sq.	16 ga. square	1.5 sq.	.065
TEN1-3A	3/8-16	1.5 sq.	11 ga. square	1.5 sq.	.120
TEN1-3B	1/2-13	1.5 sq.	11 ga. square	1.5 sq.	.120
TEN1-3C	5/8-11	1.5 sq.	11 ga. square	1.5 sq.	.120
TEN1-3D	3/4-10	1.5 sq.	11 ga. square	1.5 sq.	.120
TEN2-1A	3/8-16	2.0 sq.	16 ga. square	2.0 sq.	.065
TEN2-1B	1/2-13	2.0 sq.	16 ga. square	2.0 sq.	.065
TEN2-1C	5/8-11	2.0 sq.	16 ga. square	2.0 sq.	.065
TEN2-1D	3/4-10	2.0 sq.	16 ga. square	2.0 sq.	.065
TEN2-3A	3/8-16	2.0 sq.	11-12 ga. square	2.0 sq.	.109/.120
TEN2-3B	1/2-13	2.0 sq.	11-12 ga. square	2.0 sq.	.109/.120
TEN2-3C	5/8-11	2.0 sq.	11-12 ga. square	2.0 sq.	.109/.120
TEN2-3D	3/4-10	2.0 sq.	11-12 ga. square	2.0 sq.	.109/.120

# Polyglass Filled Nylon Tube End Adaptors



## Round

P/N	Thread (A)	O.D. (B)	Tube Gauge Shape	Tube Outside Dia.	Tube Wall
TEN1-1A	3/8-16	1.5 dia.	16 ga. round	1.5 dia.	.065
TEN1-1B	1/2-13	1.5 dia.	16 ga. round	1.5 dia.	.065
TEN1-1C	5/8-11	1.5 dia.	16 ga. round	1.5 dia.	.065
TEN1-1D	3/4-10	1.5 dia.	16 ga. round	1.5 dia.	.065
TEN1-10A	3/8-16	2.0 dia.	2.0 Sch 10 pipe	1.9 dia.	.109
TEN1-10B	1/2-13	2.0 dia.	2.0 Sch 10 pipe	1.9 dia.	.109
TEN1-10C	5/8-11	2.0 dia.	2.0 Sch 10 pipe	1.9 dia.	.109
TEN1-10D	3/4-10	2.0 dia.	2.0 Sch 10 pipe	1.9 dia.	.109
TEN2-2A	3/8-16	2.0 dia.	16 ga. round	2.0 dia.	.065
TEN2-2B	1/2-13	2.0 dia.	16 ga. round	2.0 dia.	.065
TEN2-2C	5/8-11	2.0 dia.	16 ga. round	2.0 dia.	.065
TEN2-2D	3/4-10	2.0 dia.	16 ga. round	2.0 dia.	.065

## Tube Caps

### Heavy duty plastic tube caps, Inch

P/N	Tube Size (square)	Tube Size	Gauge Size
TC1-2	1 1/2	.065	16
TC1-3	1 1/2	.120	11
TC2-3	2	.120	11-12



1-800-453-1692  
[www.aboveboardelectronics.com](http://www.aboveboardelectronics.com)

# Teardrop Polymount™ Leveling Mounts

The base on this PolyMount™ makes it easier to drill and install a lag bolt. The teardrop shape offsets the single lag hole to the outside of the machine footprint. This offset provides the clearance necessary to drill the lag bolt hole without moving the machine. Use up to a ½" diameter lag bolt.



## Specifications:

Glass-reinforced nylon base

Studs are either low carbon steel with clear zinc plating or 303 stainless steel

One-piece forged and roll-threaded stud

Inch and metric sizes

Mounts with studs furnished with jam nut

Patent Pending

## Standard Options:

Non-skid elastomer pad

SocketLock™